To: Meg Patulski[Patulski.Meg@epa.gov]

From: Berry, Laura

Sent: Fri 11/18/2016 3:57:47 PM

Subject: RE: Revised DRAFT Information for Transmittal to FHWA Regarding the I-70 East Project

Hi Meg,

Ex. 5 - Deliberative Process

Laura Berry

(734) 214-4858

berry.laura@epa.gov

From: Russ, Timothy

Sent: Friday, November 18, 2016 10:05 AM

To: Patulski, Meg <patulski.meg@epa.gov>; Berry, Laura <berry.laura@epa.gov>; Dubey,

Susmita <dubey.susmita@epa.gov>

Cc: Odendahl, Steve <Odendahl.Steve@epa.gov>; Denawa, Mai <Denawa.Mai@epa.gov>; Dresser, Chris <Dresser.Chris@epa.gov>; Anderson, Carol <Anderson.Carol@epa.gov>; Schuller, Jennifer <Schuller.Jennifer@epa.gov>; Jackson, Scott <Jackson.Scott@epa.gov>;

Rickard, Joshua < Rickard. Joshua @epa.gov>

Subject: FW: Revised DRAFT Information for Transmittal to FHWA Regarding the I-70 East

Project

Hi Everyone,

Ex. 5 - Deliberative Process

Thanks to all for your review and edits!

Tim

Tim Russ
Environmental Scientist
USEPA Region 8
Air Program
1595 Wynkoop Street (8P-AR)
Denver, CO 80202-1129
Ph. (303) 312-6479
Fax (303) 312-6064

e-mail: russ.tim@epa.gov

Ex. 5 - Deliberative Process

Ex. 5 - Deliberative Process

La Casa (CASA)

Region: Denver Monitoring Station 4545 Navajo Street

SAROAD:

AQS ID: 080310026 Latitude: 39.779460 Longitude: -105.005124

Reporting capabilities (hourly) SLAMS: CO, PM10, PM2.5

NAMS: <u>03</u>, <u>S02</u>

SPM: NO, RD, RS, TEMP, WD, WS

EPA's November, 2015 PM Hot-spot modeling guidance ("Transportation Conformity Guidance for Quantitative Hot-spot Analyses in PM_{2.5} and PM₁₀ Nonattainment and Maintenance Areas") notes the following in section 9.3.4 *24-hour PM₁₀ NAAQS*:

Calculating Design Values and Determining Conformity

The 24-hour PM₁₀ design value is calculated at each receptor by directly adding the sixth-highest modeled 24-hour concentrations (if using five years of meteorological data) to the appropriate monitor value for the 24-hour background concentration from three years of monitoring data, based on Exhibit 9-6. Exhibit 9-6: Monitor Value Used for Design Value Calculation

Number of Background Monitor Value Used for

Concentration Values from Design Value Calculation the Monitor

< 347 Highest Monitor Value
 348 -695 Second Highest Value
 696 -1042 Third Highest Value
 1043 -1096 Fourth Highest Value

PM₁₀ data from the La Casa monitoring site are provided in the table below:

POC 1 1 in 3 Sampler

Year	Ν	Highest value	2 nd highest	3 rd highest	4 th highest
2015	119	55	48	44	43
2014	127	66	65	62	62
2013	122	81	73	56	45

[&]quot;N" = the number of days of valid data recovery.

NOTE: There are actually three PM₁₀ monitors co-located at the La Casa monitoring location. POC#1 is a "1 in 3" sampler and takes a sample every 3rd day; it is our understanding that this is the primary monitor as so designated by CDPHE. POC#2 is a "1 in 6" sampler and takes a sample every 6th day and POC#3 is a continuous monitor and samples every day.

Ex. 5 - Deliberative Process

Ex. 5 - Deliberative Process

We were aware before of a Sierra Club comment on the numbers and percentage of trucks on the I-70 East project. They had presented CDOT data that showed higher percentages of trucks than appeared to be used in the I-70 East FEIS. This issue, and using Sierra Club's comments, was also raised by two Denver City Councilmembers, in a letter to EPA dated 4/26/16, as follows:

"To estimate emissions from the highway segment nearest the neighborhoods where pollution levels are expected to be the worst, COOT omitted half of expected truck emissions by using the region wide truck share (4.9%) of VMT rather than the actual truck counts on 1-70 (9.8%) reported on CDOT's website. Does the EPA rule require that emissions from actual traffic on the interstate be modeled?"

FHWA provided the below response:

"For the ROD modeling, FHWA ran MOVES2010b at the Project scale to develop lookup tables of PM₁₀ emissions rates for every possible combination of speed and grade. Separate tables of emissions rates were developed for "cars" and "trucks," as defined in the DRCOG model. To calculate total emissions for each link, these emissions rates (along with the APCD road dust emissions rates) are applied to the car and truck volumes on each link. Thus, rather than using one project-wide "truck fraction," truck emissions are explicitly calculated for each link using the reported truck volume for that link."

Ex. 5 - Deliberative Process

Ex. 5 - Deliberative Process

Ex. 5 - Deliberative Process

"Also, a close out letter from EPA is requested. We will send a draft conformity report to EPA and also send modeling input, traffic, and met data, to EPA for review during the public review. Jeff committed to send an example letter/email regarding the South Mountain project from EPA Region 9."

Ex. 5 - Deliberative Process

Please let us know if there are any questions.

Thanks!

Tim

Tim Russ Environmental Scientist USEPA Region 8 Air Program 1595 Wynkoop Street (8P-AR) Denver, CO 80202-1129 Ph. (303) 312-6479 Fax (303) 312-6064

e-mail: russ.tim@epa.gov